



# SF21G THRU SF28G

## SUPERFAST RECOVERY RECTIFIER

**REVERSE VOLTAGE:** 50 to 600 VOLTS

**FORWARD CURRENT:** 2.0 AMPERE

### FEATURES

- High surge capability
- Low forward voltage, high current capability
- Hermetically sealed
- Superfast recovery times
- Low leakage.
- Glass Passivated Die Construction
- Suffix "H" indicates Halogen-free parts, ex. SF21GH

### MECHANICAL DATA


Case : Molded plastic, DO-15

Epoxy : UL 94V-O rate flame retardant

Lead : Axial leads, solderable per MIL-STD-202,  
method 208 guaranteed

Polarity : Color band denotes cathode end

Mounting position : Any



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

Parameter	Symbols	SF21G	SF22G	SF23G	SF24G	SF25G	SF26G	SF28G	Units
Maximum Recerrent Peak Reverse Voltage	$V_{RRM}$	50	100	150	200	300	400	600	Volts
Maximum RMS Voltage	$V_{RMS}$	35	70	105	140	210	280	420	Volts
Maximum DC Blocking Voltage	$V_{DC}$	50	100	150	200	300	400	600	Volts
Maximum Average Forward Rectified Current .375"(9.5mm) Lead Length at $T_A=55^\circ\text{C}$	$I_{(AV)}$	2.0							Amp
Peak Forward Surge Current, 8.3ms single half-sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	50.0							Amp
Maximum Forward Voltage at 2.0A DC and 25°C	$V_F$	0.95				1.3		1.7	Volts
Maximum Reverse Current at $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage $T_A=100^\circ\text{C}$	$I_R$	5.0				100			uAmp
Typical Junction Capacitance (Note 1)	$C_J$	22							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	40.0							°C/W
Maximum Reverse Recovery Time (Note 3)	$T_{RR}$	35							nS
Operating and Storage Temperature Range	$T_J, T_{stg}$	-65 to +150							°C

#### NOTES:

1- Measured at 1 MHz and applied reverse voltage of 4.0 VDC.

2- Thermal Resistance Junction to Ambient and form junction to lead at 0.375"(9.5mm) lead length P.C.B. Mounted.

3- Reverse Recovery Test Conditions:  $I_F=.5A$ ,  $I_R=1A$ ,  $I_{RR}=.25A$ .



# SF21G THRU SF28G

## SUPERFAST RECOVERY RECTIFIER

### RATINGS AND CHARACTERISTIC CURVES




FIG.1 TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3 TYPICAL REVERSE CHARACTERISTICS




FIG.4 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT