

# BAV19W / BAV20W / BAV21W

## HIGH VOLTAGE SWITCHING DIODES

### FEATURES

- Fast switching speed
- Surface mount package ideally suited for automatic insertion
- Suffix "H" indicates Halogen-free parts, ex. BAV19WH

### MECHANICAL DATA


Case : SOD-123FL

Polarity : Band Indicates Cathode

Marking Code : BAV19W=H1

BAV20W=H2

BAV21W=H3



### Absolute Maximum Ratings

Tamb = 25 °C, unless otherwise specified

Parameter	Symbol	Value	Unit
Power Dissipation	$P_D$	400	mW
Maximum Repetitive Peak Reverse Voltage	$V_{RRM}$	250	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Current Pulse Width = 1.0 Second	$I_{FSM}$	1.0	A
Junction Temperature	$T_J$	150	°C
Storage Temperature Range	$T_{stg}$	-65 to +150	°C

### Electrical Characteristics

Tamb = 25 °C, unless otherwise specified


Parameter	Symbol	Test Condition	Min.	Max.	Units	
Breakdown Voltage	$B_V$	$I_R=100\mu A$	BAV19W	120	-	V
			BAV20W	200	-	
			BAV21W	250	-	
Reverse Leakage Current	$I_R$	BAV19W	$V_R=100V$	-	100	nA
		BAV20W	$V_R=150V$	-	100	
		BAV21W	$V_R=200V$	-	100	
Forward Voltage	$V_F$	$I_F=100mA$ $I_F=200mA$	-	1.0	V	
			-	1.25		
Capacitance	$C$	$V_R=0V, f=1MHz$	-	5.0	pF	
Reverse Recovery Time	$T_{RR}$	$I_F=I_R=30mA$ $R_L=100\Omega, I_{RR}=3mA$	-	50	nS	

# BAV19W / BAV20W / BAV21W


## HIGH VOLTAGE SWITCHING DIODES

### RATINGS AND CHARACTERISTIC CURVES

**Total Capacitance**



**Forward Voltage vs Ambient Temperature**



**Reverse Current vs Reverse Voltage**

