



SE03Q2BDDDBH

ESD PROTECTION DIODE

FEATURES

- High Reliability
- Bi-directional ESD Protection
- Suffix " H " indicated Halogen-free part, ex.SE03Q2BDDDBH


APPLICATIONS

- Cellular handsets and accessories
- Communication systems


MECHANICAL DATA

Case : DFN0603

PIN CONFIGURATION



Top View



Dimensions in inches and (millimeters)

Maximum Ratings (Rating at 25°C ambient temperature unless otherwise specified)

Parameter	Symbol	Value	Units
Peak Pulse Power ($t_p=8/20\mu s$)	P_{PP}	70	W
Peak Pulse Current ($t_p=8/20\mu s$)	I_{PP}	8.2	A
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Junction Temperature	T_J	125	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C



SE03Q2BDDBH

ESD PROTECTION DIODE

Electrical Characteristics (Rating at 25°C ambient temperature unless otherwise specified)

Parameter	Test Condition	Symbol	Min	Max	Units
Reverse Stand-Off Voltage	-	V_{RWM}	-	3.3	V
Reverse Breakdown Voltage	$I_R=1\text{mA}$	$V_{(BR)R}$	4.0	-	V
Reverse Leakage Current	$V_{RWM}=3.3\text{V}$	I_R	-	100	nA
Clamping Voltage	$I_{pp}=4\text{A}, t_p=8/20\mu\text{s}$	V_C	-	7.3	V
	$I_{pp}=8.2\text{A}, t_p=8/20\mu\text{s}$		-	8.5	
Junction Capacitance	$V_R=0\text{V}, f=1\text{MHz}$	C_J	-	23	pF

RATINGS AND CHARACTERISTIC CURVES




Fig.1-Pulse Waveform




Fig.2-Clamping Voltage vs. Peak Pulse Current




Fig.3-Junction Capacitance vs. Reverse Voltage





Fig.4-TLP Curve



SE03Q2BDDBH

ESD PROTECTION DIODE

TAPE & REEL SPECIFICATION



Item	Symbol	DFN0603
Carrier width	A_0	*
Carrier length	B_0	
Carrier depth	K_0	
Sprocket hole	d	1.50 ± 0.10
Reel outside diameter	D	178.00 ± 2.00
Feed hole width	D_0	13.00 ± 0.50
Reel inner diameter	D_1	MIN. 54.00
Sprocket hole position	E	1.75 ± 0.10
Punch hole position	F	3.50 ± 0.10
Sprocket hole pitch	P_0	4.00 ± 0.10
Punch hole pitch	P_1	2.00 ± 0.10
Embossment center	P_2	2.00 ± 0.10
Overall tape thickness	T	MAX. 0.60
Tape width	W	8.00 ± 0.30
Reel width	W_1	8.40 ± 1.50

ORDER INFORMATION


Part Number	Marking Code	Reel Size	Quantity
SE03Q2BDDBH	EW	7"	10,000



SE03Q2BDDDBH

ESD PROTECTION DIODE

SUGGESTED SOLDER PAD LAYOUT



Unit :mm

PACKAGE	A	B	C	D
DFN0603	0.675	0.175	0.250	0.270